REX

HEAVY DUTY

WWW.REXLUBE.COM

CERTIFIED & BONDED

THE LATEST IN **HIGH-TECHNOLOGY** LUBRICATION

– ALL PRODUCTS ARE CERTIFIED AND BONDED BY THE MANUFACTURER'S 5 MILLION DOLLAR LIABILITY INSURANCE. –

MADE IN USA

SAE 15W-40



V231130

Heavy Duty Protection
- Exceeds the latest API CK-4 / SN standards
- Enhanced rust and corrosion protection

Medium Viscosity
- Meets 2017 and newer on-highway and Tier 4 exhaust emission standards

Premium Quality
- Protection against particulate filter blocking, catalyst poisoning, and shear viscosity loss

Contains Molybdenum - Enhances performance by effectively reducing friction, resulting in improved wear resistance and enhanced protection against oxidation.

Heavy-duty engine oil is recommended for naturally aspirated, turbo-charged or supercharged diesel, gasoline, or propane vehicles and where recommended by the manufacturer.

SAE GRADE	Heavy Duty	15W-40
API SERVICE		CK-4 / SN
API Gravity	ASTM D287	31.14
Flash Point, COC °C/°F	ASTM D92	209 / 408,2
Pour Point, °C/°F	ASTM D97	-34 / -29.2
Viscosity @ 40°C, cSt	ASTM D445	112.70
Viscosity @ 100°C, cSt	ASTM D445	15.4
Viscosity Index	ASTM D2270	139
CCS, mPa-sec °C max	ASTM D5293	5153 @ -20
Total Base No. TBN	ASTM D2896	10.2

MEETS OR EXCEEDS OEM PERFORMANCE STANDARDS

- API SN PLUS, SN, SM, SL
- API CK-4, CJ-4, CI-4 PLUS
- API CI-4, CH-4, CF-4, CF-2, CF
- ACEA E6, E7, E9
- ALLISON C-4, TES 439
- CAT ECF-3, ECF-2, ECF 1, TO-2
- CUMMINS CES 20071/20078
- CUMMINS CES 20081/20086/20092
- DETROIT DIESEL 93K222/93K218
- DEUTZ DQC III-10LA
- FORD WSS-M2C171-F1
- GLOBAL DHD-1
- GM 9985930
- IVECO 18-1804 TLS E9
- JASO DH-2, DH-1
- JOHN DEERE TIER IV ENGINES
- KOMATSU
- MACK EOS-4.5, EO-O PREMIUM PLUS
- MACK EO-M, EO-N
- MAN 3271-1/3275/3477/3575
- MB 228.31
- MTU TYPE 2.1
- NAVISTAR
- RENAULT RLD-4, RLD-3, RLD-2
- SCANIA UHPD, LDF-3, LDF-2
- VOLVO VDS-4.5, -4, -3, -2,

Typical Characteristics Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to REX (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.